

Xprinter®

Impact Dot matrix Printer


XP-C76IIN

- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing



XP-C76IIN

Impact Dot matrix Printer



Printing	
Printing method	XP-C76IIN 9-Pin serial impact dot-matrix printing
Printing width	63.5mm
Column capacity	400 dots/line
Printing speed	4.5 line/s
Interface	USB / Parallel / Serial / Lan
Printing paper	75.5±0.5mm×φ80mm(max)
Line spacing	4.23mm (Adjustable by commands)
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese, traditional Chinese: 2.7×2.7mm (16×16 dots)
Column number	76mm paper: Font A - 32 columns /Font B - 42 columns / Chinese, traditional Chinese - 16 columns
Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Power	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A
Cutter	
Auto cutter	Partial
Physical characteristics	
Weight	1.28KG
Dimensions	220×150×140mm (D×W×H)
Environmental Requirements	
Work environment	0 ~ 45°C, 10 ~ 80% RH
Storage environment	-10 ~ 60°C, 10 ~ 90% RH (no condensation)
Reliability	
Printer head life	10 Million Lines
Cutter life	1 Million



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
[Http://www.xprintertech.com](http://www.xprintertech.com)
Email: overseas@xprinter.net

